

PRODUCT INFORMATION			
SORT: CLOTH TAPE		TYPE: D117	
CONSTRUCTION	RELEASE	CARRIER: Polyethylene/Cloth	Adhesive: Hot Melt
<p>Following data just for reference. the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.</p>			
Item	Unit	Data	Test Standard
Total Thickness	170 micron $\pm$ 10micron	250 $\pm$ 5 %	GB/7125-1999
Backing	PE-Laminated Cloth	---	---
Peel Adhesion (to stainless steel)	$\geq$ 16.5 N/25mm	$\geq$ 12	GB/2792-1998
Tensile Strength	$\geq$ 80 N/25mm	$\geq$ 70	GB/7753-1987
<p>Characteristic: It enjoys high tensile strength, good moisture resistance, easy tear and it conforms well to irregular surface.</p>			
<p>Applications: Suitable for carton sealing, carpet joint, Light duty packaging, bundling</p>			
<p>Color: Grey, Green, Black, White, Red, blue, yellow ,brown</p>			
<p>Storage and transportation conditions:</p> <ul style="list-style-type: none"> <li>● Tape should be stored in temperature 20°C-30°C, dry 50%-70% humidity area away from direct sunlight, air conditioner and other heat sources.</li> <li>● Tape jumbos should be placed vertically with good package and avoid to be pressed against glue surface.</li> <li>● Tape should be used within 12 months from the date of production.</li> </ul>			
<p>Remarks: Surface that the tape is applied to should be clean, dry and free of grease, oil, moisture, dirt and other conditions.</p>			
<p>Conforms to Rohs and Reach</p>			
<p>Additions: The users should try first for small quantity, and determine whether the product is suitable for his particular applications before large quantity.</p>			
<p>Issued date: 2024-2-15</p>			