

PRODUCT INFORMATION

508265

DESCRIPTION

Single sided packaging tape.

PRODUCT DATA

Backing	0.035 mm BOPP film
Adhesive	Natural rubber and resins; transparent, brown

	Unit	Value	Method
Total thickness	mm	0.060	PSTC 133
Adhesion to steel	N/25mm	1.45	PSTC 101
Tensile strength MD	N/25mm	125	PSTC 131
Elongation at break	%	155	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

High tensile low noise carton sealing tape, suitable for hand application.

Features	Benefits	
Natural rubber and resins adhesive	✓ Good adhesion in several applications ✓ Performing even at low temperature *	✓ Suitable for use on most recycled cartons ✓ Low noise unwinding
*Suggested application at room temperature over 10°C before storing sealed items at lower temperature		
BOPP backing	✓ High tensile strength	

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of our knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.