

PRODUCT INFORMATION

502200

DESCRIPTION

Single sided transparent tape.

PRODUCT DATA

Backing	0.028mm BOPP film
Adhesive	Synthetic rubber and resins

	Unit	Value	Method
Total thickness	mm	0.046	PSTC 133
Adhesion to steel	N/25mm	13	PSTC 101
Tensile strength MD	N/25mm	50	PSTC 131
Elongation at break	%	40	PSTC 131

APPLICATION

Single sided tape fit for school, office, stationery and home applications. Suitable for general purpose uses, easy unwinding and tear. Available in several sizes and packaging.

Features	Benefits	
Synthetic rubber and resins adhesive	✓ High tack	✓ Performing well in most common uses
BOPP backing	✓ Easy to use	✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of our knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.