

No Noise Tapes



Backing: BOPP film
Adhesive: Acrylic water based
Colour: Brown Transparent White

- No-Noise unwinding
- Wide application possibilities for manual and machine packaging
- Good resistance and tack



Material Informations

Code	Width (mm)	Length (m)
4030	38, 48, 50, 75	50, 66, 100, 132, 180

Technical Informations

Total Grammature		Total Thickness		Adhesion to Steel Plate		Tensile Strength		Elongation	
28 mμ	± 3%	46 mμ	± 6%	230 gr/cm	± 10%	4,5 Kg/cm	± 10%	150 %	± 10%

Storage Conditions

- We recommend a storage temperature between 18 and 30 °C.
- The product should not be directly exposed to heat or humidity.
- The product should be conditioned to room temperature before use.

All the above mentioned values in Technical Informations are to be considered as average values of our standard production and cannot be taken as product specifications. The products can present a ±2% tolerance in width and length. We recommend all our customers to make sure that the products is acceptable through preliminary test.

Certified Systems

UNI-EN ISO 9001:2008 n° IT244111
UNI-EN ISO 14001:2004 n° IT246656
UNI-EN ISO 18001:2007 n° IT249944
EMAS REGISTRATION n°IT001596

Revised: 01/06/2022

