

## PRODUCT INFORMATION

# 501515

### DESCRIPTION

Medium tensile mono-directional fiber glass reinforced single sided tape.

### PRODUCT DATA

<b>Backing</b>	Glass fiber reinforced + BOPP film
<b>Adhesive</b>	Synthetic rubber and resins

	<b>Unit</b>	<b>Value</b>	<b>Method</b>
<b>Total thickness</b>	mm	0.110	PSTC 133
<b>Adhesion to steel</b>	N/25mm	21	PSTC 101
<b>Tensile strength MD</b>	N/25mm	700	PSTC 131
<b>Elongation at break</b>	%	6	PSTC 131
<b>Temp. Resistance</b>	°C	60°C	=

### APPLICATION

Medium tensile mono-directional reinforced tape suitable for bundling and carton reinforcement, even used to bundle metal plates or bars.

<b>Features</b>	<b>Benefits</b>	
Synthetic rubber and resins adhesive	✓ High adhesion in most situations	✓ Excellent application results on different surfaces
Mono-directional glass fiber reinforced backing	✓ Good resistance to break ✓ Easy handling	✓ High security in application

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of our knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.