

PRODUCT INFORMATION

508317

DESCRIPTION

Single sided packaging tape.

PRODUCT DATA

Backing	0.028 mm BOPP film
Adhesive	Synthetic rubber and resins; transparent, white, brown

	Unit	Value	Method
Total thickness	mm	0.045	PSTC 133
Adhesion to steel	N/25mm	10	PSTC 101
Tensile strength MD	N/25mm	110	PSTC 131
Elongation at break	%	173	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Standard carton sealing tape, suitable for most common use.

Features	Benefits	
Synthetic rubber and resins adhesive	✓ High tack	✓ Performing well in most common use
BOPP backing	✓ Well adaptable to different shapes	✓ Good elongation

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of our knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.