

PRODUCT INFORMATION

502125

DESCRIPTION

Single sided packaging tape.

PRODUCT DATA

Backing	0.033 mm PVC film
Adhesive	Natural rubber and resins; white, brown, transparent

	Unit	Value	Method
Total thickness	mm	0.055 (white) 0.055 (brown) 0.054 (transparent)	PSTC 133
Adhesion to steel	N/25mm	3.7 (white) 3.5 (brown) 3.1 (transparent)	PSTC 101
Tensile strength MD	N/25mm	120	PSTC 131
Elongation at break	%	70	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Single sided carton sealing tape, suitable for use on standard and most recycled cartons; available in white, brown and transparent version.

Features	Benefits
Natural rubber and resins adhesive	✓ Good adhesion in several applications ✓ Performing even at low temperature * *Suggested application at room temperature over 15°C before storing sealed items at lower temperature
PVC backing	✓ Well adaptable to uneven shapes ✓ Good elongation ✓ Suitable for use on most recycled cartons ✓ No noise unwinding

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of our knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.