

PRODUCT INFORMATION

501050

22.8.2025

DESCRIPTION

Double sided adhesive tape.

PRODUCT DATA

Backing	PET fabric
Adhesive	Synthetic rubber and resins; white
Liner	Double sided siliconized paper; brown

	Unit	Value	Method
Total thickness (without Liner)	mm	0.235	PSTC 133
Adhesion to steel	N/25mm	Int: 25 – Ext: 30	PSTC 101
Tensile strength MD	N/25mm	80	PSTC 131
Elongation at break	%	15	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Standard double sided carpet tape, given its high tack and adhesive mass, it is the best choice to work on rough flooring. Not resistant to plasticizers.

Features	Benefits
Synthetic rubber and resins adhesive	<ul style="list-style-type: none"> ✓ High tack and high adhesion level both sides ✓ Suitable for most kind of carpets ✓ Excellent adhesion on rough surfaces
PET fabric backing	<ul style="list-style-type: none"> ✓ Highly adaptable to various shapes ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of our knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.